article#	**253832-soc**
article description	**3-way connector TopTaurus2 rubber hinged lid nat SH LED IP54 orange**
description long	3-way connector TopTaurus2 rubber with hinged lid color housing/terminal-cover: black/orange contact carrier: polyamide ready wired on 3-pole terminal block (PH1) earthing system: Austrian/German with shutter (type F - with earth lug) contacts: nickel plated 250V~ / 16A / 2P+E external strain relief with gland nut, with LED voltage indicator light for serve conditions protection rating: IP54
country of origin	AT
customs number	85366990
packaging quantitiy	5
minimum order quantitiy	50



ETIM 10.0	EC001327
Model	Coupler with protective contact CEE 7/3 (type F)
Material	Rubber
Material quality	Thermoplastic
Degree of protection (IP)	IP54
Insert direction	Straight
Connection system	Screwed terminal
With voltage indication	True
Colour	Orange
Number of poles	3
Nominal voltage	250 V
Nominal current	16 A
For heavy conditions according to VDE	True

K (cable Ø)	6-19 mm
wire flexible	1-2,5 mm²
contact screws	50 Ncm
housing screws	160 Ncm
strain relief	400 Ncm
dismantling length	30 mm
stripping length	7 mm
ambient temperature	-25 – 40 °C



https://www.pcelectric.at/shop/en/?func=detail&artnr=253832-soc

Changes and printing errors reserved!

(C) PC ELECTRIC Ges.m.b.H. - Diesseits 145 - 4973 St. Martin i.I. - Austria - www.pcelectric.at