

PCE data sheet

article#	31492-12v
article description	CEE-receptacle flange 75x75 straight 20A 3P4W 12h IP67 UL
description long	CEE-receptacle flange 75x75 straight 20A 3P4W 12h IP67 UL (PCE420R12Wv) housing material: PA6 rated current: 20A number of poles: 3P4W (4p) clock position: 12h rated voltage: 120/250Vac single phase contacts: brass nickel plated connection technology: screw terminals dimensions (flange/fixing center): 75x75mm / 60x60mm IP protection class: IP67
country of origin	AT
customs number	85366990

ETIM 7.0	EC001317
IEC-amperage	
Amperage acc. UL/CSA (for UL-version)	20 A
Number of poles	4
Clock hour position	12 h
Identification colour	
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface finish contacts	Nickel-plated
Flange size vertical	75 mm
Drill hole distance vertical	60 mm
Flange size horizontal	75 mm
Drill hole distance horizontal	60 mm

wire flexible	1-2,5 mm ²
wire solid	1-4 mm ²
contact screws	100 Ncm
dismantling length	50 mm
stripping length	10-12 mm



www.manufacturer-safety.info