

PCE data sheet

article#	42492-12f78
article description	CEE-receptacle flange 80x97 angled 30A 3P4W 12h IP67 UL
description long	CEE-receptacle flange 80x97 angled 30A 3P4W 12h IP67 UL (PCE430RA12W) housing material: PA6 rated current: 30A number of poles: 3P4W (4p) clock position: 12h rated voltage: 120/250Vac single phase contacts: brass connection technology: screw terminals dimensions (flange/fixing center): 80x97mm / 60x73mm IP protection class: IP67
country of origin	AT
customs number	85366990

ETIM 7.0	EC001317
IEC-amperage	
Amperage acc. UL/CSA (for UL-version)	30 A
Number of poles	4
Clock hour position	12 h
Identification colour	
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Angled
Material	Plastic
Contact material	CuZn
Surface finish contacts	Untreated
Flange size vertical	97 mm
Drill hole distance vertical	73 mm
Flange size horizontal	80 mm
Drill hole distance horizontal	60 mm

wire flexible	2,5-6 mm ²
wire solid	2,5-10 mm ²
contact screws	110 Ncm
dismantling length	50 mm
stripping length	12-14 mm



www.manufacturer-safety.info