


PCE data sheet

| | |
|------------------------|--|
| article# | 80242-6tt |
| article description | CEE angled plug 32A 4p 6h IP67 TT TWIST |
| description long | CEE angled plug 32A 4p 6h IP67 TT TWIST housing material: PC/ABS rated current: 32A number of poles: 4 (3P+PE) clock-position: 6h rated voltage/frequency: 380-415V~ / 50+60Hz contacts: brass connection technology: screwless terminals (TT) IP protection class: IP67 |
| GTIN (EAN) | 9003399333309 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.238 kg |
| packaging quantity | 10 |
| minimum order quantity | 10 |

| | |
|----------------------------|----------------------|
| ETIM 8.0 | EC000140 |
| IEC-amperage | 32 A |
| Number of poles | 4 |
| Voltage acc. EN 60309-2 | 400 V (50+60 Hz) red |
| Clock hour position | 6 h |
| Identification colour | Red |
| Degree of protection (IP) | IP67 |
| Connection system | Screw less terminal |
| Cable entry | Swivel |
| Angle of plug | Angled |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Untreated |

| | |
|--------------------|-----------------------|
| a | 126 mm |
| b | 93 mm |
| c | 110 mm |
| d | 25 ° |
| K (cable Ø) | 11,5-20 mm |
| SW | 50 mm |
| wire flexible | 2,5-6 mm ² |
| strain relief | 600 Ncm |
| dismantling length | 50 mm |
| stripping length | 12-14 mm |



<https://www.pcelectric.at/shop/en/?func=detail&artnr=80242-6tt>



www.manufacturer-safety.info