

PCE data sheet

| | |
|---------------------|---|
| article# | 0149-5v |
| article description | CEE-plug 20A 3P4W 5h IP44 UL |
| description long | CEE-plug 20A 3P4W 5h IP44 UL (PCE420P5Sv) housing material: PA6 rated current: 20A number of poles: 3P4W (4p) clock position: 5h rated voltage: 600Vac contacts: brass nickel plated connection technology: screw terminals IP protection class: IP44 |
| country of origin | AT |
| customs number | 85366990 |

| | |
|---------------------------------------|------------------|
| ETIM 7.0 | EC000140 |
| IEC-amperage | |
| Amperage acc. UL/CSA (for UL-version) | 20 A |
| Number of poles | 4 |
| Clock hour position | 5 h |
| Identification colour | Black |
| Degree of protection (IP) | IP44 |
| Connection system | Screwed terminal |
| Cable entry | Swivel |
| Angle of plug | Straight |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |

| | |
|--------------------|-----------------------|
| a | 128 mm |
| b | 92 mm |
| c | 53 mm |
| K (cable Ø) | 9-15 mm |
| SW | 42 mm |
| wire flexible | 1-2,5 mm ² |
| contact screws | 100 Ncm |
| strain relief | 500 Ncm |
| dismantling length | 50 mm |
| stripping length | 10-12 mm |

