

## PCE data sheet

article#	<b>42492-7f78</b>
article description	<b>CEE-receptacle flange 80x97 angled 30A 3P4W 7h IP67 UL</b>
description long	CEE-receptacle flange 80x97 angled 30A 3P4W 7h IP67 UL (PCE430RA7W) housing material: PA6 rated current: 30A number of poles: 3P4W (4p) clock position: 7h rated voltage: 480Vac contacts: brass connection technology: screw terminals dimensions (flange/fixing center): 80x97mm / 60x73mm IP protection class: IP67
GTIN (EAN)	9003399438325
country of origin	AT
customs number	85366990
net weight	0.224 kg
packaging quantity	10

ETIM 7.0	EC001317
IEC-amperage	
Amperage acc. UL/CSA (for UL-version)	30 A
Number of poles	4
Clock hour position	7 h
Identification colour	Red
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Angled
Material	Plastic
Contact material	CuZn
Surface finish contacts	Untreated
Flange size vertical	97 mm
Drill hole distance vertical	73 mm
Flange size horizontal	80 mm
Drill hole distance horizontal	60 mm

wire flexible	2,5-6 mm <sup>2</sup>
wire solid	2,5-10 mm <sup>2</sup>
contact screws	110 Ncm
dismantling length	50 mm
stripping length	12-14 mm



[www.manufacturer-safety.info](http://www.manufacturer-safety.info)